

MODULE B: EU TYPE-EXAMINATION – PRODUCTION TYPE

Issued by DBI Certification, notified body no. 2531


The equipment identified below which was found to be in compliance with the essential requirements of the Regulation of Appliance burning gaseous fuels (EU) 2016/426 Annex III, 1, subject to any conditions in the description attached hereto.

Manufacturer	Integrated Gas Technologies ApS
Address	Gydevang 39-41, DK-3450, Allerød, Denmark
Type of Appliance	Regulator
Trade Mark	IGT
Pin Code	2531CS-0136
Specified Standards	EN 16129:2013 & EN 12864:2001+A1:2003+A2:2005+A3:2009* *EN 12864 and all of its amendments are withdrawn and covered by EN 16129
Issue Date	2022-02-24
Expiration Date	2028-04-21
First Issued	2018-04-21

The certificate supersedes the certificate version issued: 2021-12-15 by NB no. 2531

Signed

Name


 Jesper Viggo Quaade
 Responsible for evaluation


 Lene Skovbjerg
 Responsible for certification decision

Note:

This certificate will not be valid if the manufacturer makes any changes or modifications to the approved equipment, which have not been notified to, and agreed with the notified body named on this certificate. Demonstration of full compliance with the Gas Appliance Regulation (EU) 2016/426 and EU Surveillance Certificate (EU Declaration of Conformity to Type) is required.

This certificate remains valid unless suspended or withdrawn, provided the conditions in the attached description are complied with and the equipment remains satisfactory in service.

Models	A300i and A310i
---------------	-----------------

Category	Pressure [mbar]	Country of destination
I _{3B}	28-30	All EU
I _{3P}	30, 37, 50	
I _{3B/P}	28-30, 50	

Test reports	SGS test report SDHL1711024306GA-01, 2020-12-18, Amendment-1: 2020-12-18, Amendment-2: 2021-08-12 & Amendment-3: 2022-01-19.
---------------------	--

Gas type:	Butane	Propane			LPG	
Flow rate/Capacity [kg/h]:	1.5	1.5			0.8	
Inlet pressure [bar]:	0.3 – 7.5	1 - 16			0.3 – 16	
Outlet pressure [mbar]:	28-30	30	37	50	28-30	50
Inlet connection:	Male (A300i): G7, G9, G10 Female (A310i): G1, G2, G4, G5, G6, G8, G11, G12, EN417-7/16"					
Outlet connection:	H1, H4(1/4"), H50, H51					
Working temperature:	0°C ~ 50°C	-20°C ~ 50°C			-20°C ~ 50°C	

End of Certificate

